



## - AGRICULTURAL TIRE

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure	Pattern
					(mm)	(mm)		Inflate	
									(kPa)
6.00-14	6	R1	5.00	TL	155	627	268	190	C1C0004
7.00-14	6	R1	6.00	TL	183	690	317	160	C1C0004
7.00-16	6	R1	6.00	TL	183	741	446	250	C1C0004
8.00-16	6	R1	6.00	TL	210	790	549	190	C1C0004



Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure	Pattern
					(mm)	(mm)		Inflate	
									(kPa)
10.0/80-12	10	R1	10.00	TL	264	708	1000	390	C1C0012
6.00-14	4	R1	5.00	TL	150	630	288	190	C1C0012
7.00-14	4	R1	6.00	TL	180	695	341	160	C1C0012
31x15.5-15	8	R1	13.00	TL	391	792	1250	310	C1C0012
31x15.5-15	12	R1	13.00	TL	391	792	1700	520	C1C0012
7.00-16	6	R1	6.00	TL	182	747	480	250	C1C0012
7.50-16	6	R1	6.00	TT	214	803	1046	290	C1C0012
7.50-16	8	R1	6.00	TT	214	803	1305	415	C1C0012
8.00-16	6	R1	6.00	TL	207	790	590	190	C1C0012
8.3-20	6	R1	7.00	TT	210	895	681	240	C1C0012
7.50-20	6	R1	6.00	TT	214	904	1132	290	C1C0012
7.50-20	8	R1	6.00	TT	214	904	1439	415	C1C0012
9.5-20	6	R1	8.00	TT	240	950	815	220	C1C0012
8.3-24	6	R1	7.00	TT	211	995	767	240	C1C0012
8.3-24	8	R1	7.00	TT	211	995	887	310	C1C0012
9.5-24	6	R1	8.00	TT	232	1056	911	210	C1C0012
9.5-24	8	R1	8.00	TT	232	1056	1074	280	C1C0012
11.2-24	6	R1	10.00	TT	284	1105	1016	180	C1C0012
11.2-24	8	R1	10.00	TT	284	1105	1198	240	C1C0012
12.4-24	4	R1	11.00	TT	315	1160	910	110	C1C0012
12.4-24	6	R1	11.00	TT	315	1160	1164	170	C1C0012
12.4-24	8	R1	11.00	TT	315	1160	1389	230	C1C0012
13.6-24	8	R1	12.00	TT	345	1210	1437	190	C1C0012
14.9-24	4	R1	13.00	TT	378	1245	1073	80	C1C0012
14.9-24	6	R1	13.00	TT	378	1265	1485	140	C1C0012
14.9-24	8	R1	13.00	TT	378	1265	1725	180	C1C0012



## - AGRICULTURAL TIRE

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure	Pattern
					(mm)	(mm)		Inflate	
					(kgs)	(kPa)			
16.9-24	6	R1	15.00	TT	429	1335	1677	130	C1C0012
16.9-24	8	R1	15.00	TT	429	1335	1974	170	C1C0012
11.2-28	6	R1	10.00	TT	284	1205	1073	180	C1C0012
11.2-28	8	R1	10.00	TT	284	1205	1265	240	C1C0012
12.4-28	6	R1	11.00	TT	325	1260	1212	170	C1C0012
12.4-28	8	R1	11.00	TT	325	1260	1485	230	C1C0012
12.4-28	12	R1	11.00	TT	325	1260	1581	250	C1C0012
13.6-28	8	R1	12.00	TT	345	1310	1581	200	C1C0012
14.9-28	6	R1	13.00	TT	378	1365	1581	140	C1C0012
14.9-28	8	R1	13.00	TT	378	1365	1821	180	C1C0012
16.9-28	8	R1	15.00	TT	429	1435	2089	170	C1C0012
16.9-28	10	R1	15.00	TT	429	1435	2329	200	C1C0012
16.9-28	12	R1	15.00	TT	429	1435	2612	240	C1C0012
16.9-30	10	R1	15.00	TT	429	1485	2468	200	C1C0012
18.4-30	8	R1	16.00	TT	460	1545	2329	140	C1C0012
18.4-30	10	R1	16.00	TT	460	1545	2779	180	C1C0012
18.4-30	12	R1	16.00	TT	460	1545	3114	230	C1C0012
18.4-30	14	R1	16.00	TT	460	1545	3306	260	C1C0012
18.4-34	8	R1	16.00	TT	467	1650	2539	140	C1C0012
18.4-34	10	R1	16.00	TT	467	1650	2874	180	C1C0012
18.4-34	12	R1	16.00	TT	467	1650	3209	230	C1C0012
11.2-38	6	R1	10.00	TT	287	1455	1255	180	C1C0012
13.6-38	6	R1	12.00	TT	345	1565	1629	160	C1C0012
13.6-38	8	R1	12.00	TT	345	1565	1869	200	C1C0012
13.6-38	12	R1	12.00	TT	345	1565	2329	290	C1C0012
15.5-38	8	R1	14.00	TT	395	1585	1974	180	C1C0012
16.9-38	8	R1	15.00	TT	429	1685	2468	170	C1C0012
16.9-38	10	R1	15.00	TT	429	1685	2612	200	C1C0012
16.9-38	12	R1	15.00	TT	429	1685	2876	230	C1C0012
18.4-38	8	R1	16.00	TT	467	1750	2612	140	C1C0012
18.4-38	12	R1	16.00	TT	467	1750	3499	230	C1C0012
20.8-38	8	R1	18.00	TT	530	1835	3020	130	C1C0012
20.8-38	12	R1	18.00	TT	530	1835	3835	200	C1C0012





## - Tractor Front Tyres



Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure Inflate	Pattern
					(mm)	(mm)			
4.00-12	4	F2	3.00	TT/TL	109	534	224	360	C1C0001
5.00-15	6	F2	3.00	TT/TL	130	660	375	390	C1C0001
7.5L-15	6	F2	6.00	TT/TL	206	741	650	300	C1C0001
9.5L-15	8	F2	7.00	TT/TL	244	780	850	330	C1C0001
11L-15	8	F2	8.00	TT/TL	277	810	950	300	C1C0001
5.50-16	6	F2	4.00	TT/TL	147	713	475	390	C1C0001
6.00-16	6	F2	4.00	TT/TL	159	739	515	360	C1C0001
6.50-16	6	F2	4.50	TT/TL	170	756	560	330	C1C0001
7.50-16	8	F2	5.50	TT/TL	206	803	775	390	C1C0001
10.00-16	8	F2	8.00	TT/TL	272	892	1060	300	C1C0001
11.00-16	8	F2	10.00	TT/TL	320	965	1180	280	C1C0001
4.00-19	4	F2	3.00	TT/TL	112	718	325	360	C1C0001
7.50-18	8	F2	5.50	TT/TL	203	853	850	390	C1C0001
7.50-20	8	F2	5.50	TT/TL	203	904	900	390	C1C0001

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure Inflate	Pattern
					(mm)	(mm)			
10.00-16	8	F2	8.00	TT/TL	272	892	1060	300	C1C0002
11.00-16	8	F2	10.00	TT/TL	320	965	1180	280	C1C0002

