



agtire.apexway.com.tw

**- Agricultural Implement Tire - Non Traction**



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
7.00-12	6	11	5.50	TT/TL	200	657	620	360	C1C0006
7.00-12	12	11	5.50	TT/TL	200	657	1800	860	C1C0006
10.0/80-12	8	11	9.00	TL	264	710	1250	420	C1C0006
10.0/80-12	10	11	9.00	TT/TL	264	710	1360	390	C1C0006
10.0/80-12	10	11	9.00	TL	264	710	1450	540	C1C0006
10.0/75-15.3	8	11	9.00	TT/TL	264	760	1360	310	C1C0006
10.0/75-15.3	10	11	9.00	TT/TL	264	760	1550	390	C1C0006
10.0/75-15.3	12	11	9.00	TT/TL	264	760	1700	470	C1C0006
10.0/75-15.3	14	11	9.00	TT/TL	274	760	1900	710	C1C0006
10.0/75-15.3	18	11	9.00	TT/TL	264	760	2360	710	C1C0006
11.5/80-15.3	10	11	9.00	TT/TL	290	845	1950	340	C1C0006
11.5/80-15.3	12	11	9.00	TL	297	844	2180	560	C1C0006
11.5/80-15.3	14	11	9.00	TT/TL	290	845	2430	475	C1C0006
11.5/80-15.3	16	11	9.00	TT/TL	290	845	2575	510	C1C0006
11.5/80-15.3	18	11	9.00	TT/TL	290	845	2725	600	C1C0006
12.5/80-15.3	12	11	9.00	TT/TL	307	889	2430	370	C1C0006
12.5/80-15.3	14	11	9.00	TT/TL	307	889	2650	430	C1C0006
12.5/80-15.3	16	11	9.00	TT	312	885	2800	650	C1C0006
12.5/80-15.3	18	11	9.00	TT/TL	307	889	3000	540	C1C0006
400/60-15.5	10	11	13.00	TL	405	875	2240	360	C1C0006
400/60-15.5	14	11	13.00	TT/TL	403	868	2500	360	C1C0006
400/60-15.5	16	11	13.00	TT/TL	403	868	2900	400	C1C0006
400/60-15.5	18	11	13.00	TL	405	875	3450	620	C1C0006
10.5/65-16	10	11	9.00	TT/TL	273	754	1550	380	C1C0006
10.5/65-16	10	11	9.00	TL	274	755	1550	520	C1C0006
10.5/65-16	14	11	9.00	TT/TL	273	754	1900	530	C1C0006
10.5/65-16	14	11	9.00	TL	274	755	1900	710	C1C0006
10.5/80-18	10	11	9.00	TL	273	885	2180	430	C1C0006
13.0/65-18	16	11	11.00	TT/TL	335	889	2800	490	C1C0006
13.0/65-18	12	11	11.00	TL	336	890	2360	490	C1C0006
13.0/65-18	14	11	11.00	TL	336	890	2575	580	C1C0006
12.5/80-18	14	11	11.00	TL	308	986	3000	430	C1C0006



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
10.0/80-12	8	11	9.00	TL	264	710	1250	420	C1C0008
10.0/80-12	10	11	9.00	TL	264	710	1450	540	C1C0008



**- Agricultural Implement Tire - Non Traction**



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
400/60-15.5	10	I1	13.00	TL	405	875	2240	350	C1C0009
400/60-15.5	14	I1	13.00	TL	404	868	2900	360	C1C0009
400/60-15.5	16	I1	13.00	TL	404	868	3250	400	C1C0009
13.0/65-18	12	I1	11.00	TL	336	890	2360	490	C1C0009
13.0/65-18	14	I1	11.00	TL	336	890	2575	580	C1C0009
13.0/65-18	16	I1	11.00	TL	336	890	2800	670	C1C0009

Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
15.0/55-17	10	I1	13.00	TL	391	850	2120	360	C1C0018
15.0/55-17	12	I1	13.00	TL	391	850	2360	420	C1C0018
15.0/55-17	14	I1	13.00	TL	391	848	2575	360	C1C0018
15.0/55-17	18	I1	13.00	TL	391	848	3250	460	C1C0018
19.0/45-17	14	I1	16.00	TL	490	863	2800	390	C1C0018
19.0/45-17	18	I1	16.00	TL	490	863	3250	340	C1C0018
500/50-17	14	I1	16.00	TL	500	933	3250	360	C1C0018
500/50-17	18	I1	16.00	TL	500	933	4000	440	C1C0018



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
11L-16	12	F3	8.00	TL	279	838	1250	440	C1C0003



**- Agricultural Implement Tire - Non Traction**

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure	Pattern
					(mm)	(mm)		Inflate	
					(kPa)				
9.5L-14	8	11	7.00	TT/TL	244	739	1145	300	C1C0005
11L-14	6	11	8.00	TT/TL	275	747	972	190	C1C0005
5.90-15	4	11	4.50	TT/TL	157	663	541	250	C1C0005
6.70-15	8	11	4.50	TT/TL	170	701	998	390	C1C0005
7.60-15	8	11	5.50	TT/TL	191	729	998	360	C1C0005
9.5L-15	8	11	7.00	TT/TL	241	766	1177	300	C1C0005
9.5L-15	12	11	7.00	TT/TL	241	766	1366	390	C1C0005
11L-15	8	11	8.00	TT/TL	279	777	1208	250	C1C0005
11L-15	10	11	8.00	TL	279	777	1060	520	C1C0005
11L-15	12	11	8.00	TT/TL	279	777	1523	350	C1C0005
11L-15	12	11	8.00	TL	279	777	1190	620	C1C0005
11L-15	14	11	8.00	TL	279	777	1295	730	C1C0005
12.5L-15	8	11	10.00	TT/TL	317	822	1428	250	C1C0005
12.5L-15	8	11	10.00	TL	317	822	2025	410	C1C0005
12.5L-15	10	11	10.00	TT/TL	317	822	1628	300	C1C0005
12.5L-15	12	11	10.00	TT/TL	317	822	1838	360	C1C0005
12.5L-15	12	11	10.00	TL	317	822	1800	730	C1C0005
11L-16	8	11	8.00	TT/TL	279	544	1276	250	C1C0005
14L-16.1	10	11	11.00	TT/TL	355	985	1996	250	C1C0005
14L-16.1	14	11	11.00	TT/TL	355	985	2479	360	C1C0005
16.5L-16.1	10	11	14.00	TL	419	1071	2479	250	C1C0005
16.5L-16.1	12	11	14.00	TT/TL	424	1029	2705	280	C1C0005
16.5L-16.1	14	11	14.00	TL	419	1071	3046	330	C1C0005



Dot  
Dot  
Dot  
Dot



## - Agricultural Implement Tire - Traction



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
10.5/80-18	10	R4	9.00	TL	273	906	1360	370	C1C0019
12.5/80-18	12	R4	11.00	TL	308	986	1850	370	C1C0019
19.5L-24	12	R4	16.00	TL	495	1314	3450	230	C1C0019

Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
4.00-10	4	R1	3.00	TL	111	475	144	240	C1C0020
5.00-10	4	R1	4.00	TL	144	525	210	200	C1C0020



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
5.00-12	6	R1	4.00	TL	144	577	224	200	C1C0022
6.5/80-12	4	R1	5.00	TT	163	588	545	310	C1C0022
6.5/80-12	6	R1	5.00	TL	162	588	450	360	C1C0022
5.00-15	4	R1	3.00	TT/TL	144	656	475	290	C1C0022
5.00-15	6	R1	4.00	TT	145	657	600	480	C1C0022
6.5/80-15	4	R1	5.00	TL	163	663	825	490	C1C0022
6.5/80-15	6	R1	5.00	TL	162	663	550	360	C1C0022

Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
5.00-12	4	R1	4.00	TL	142	577	300	210	C1C0015
10.0/75-15.3	10	R1	9.00	TL	264	780	1090	300	C1C0015
10.0/75-15.3	12	R1	9.00	TL	264	780	1180	400	C1C0015
11.5/80-15.3	10	R1	9.00	TL	290	867	1360	340	C1C0015
11.5/80-15.3	14	R1	9.00	TL	290	867	1700	475	C1C0015





## - Agricultural Implement Tire - Traction



Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
6.00-16	8	R1	4.50	TT	169	735	750	350	C1C0016
6.50-16	8	R1	5.50	TT	188	750	650	250	C1C0016
7.50-16	6	R1	6.00	TT	214	803	975	290	C1C0016
7.50-16	8	R1	6.00	TT	214	803	1215	415	C1C0016
8.25-16	8	R1	6.00	TT	229	848	925	300	C1C0016
280/70-16	8	R1	9.00	TT/TL	282	793	1120	240	C1C0016
250/80-18	8	R1	8.00	TT/TL	250	866	1120	240	C1C0016
280/70-18	8	R1	9.00	TT/TL	282	848	1180	240	C1C0016

Size	P.R.	TRA	Rim	TT/TL	S.W. (mm)	O.D. (mm)	Max Load (kgs)	Pressure Inflate (kPa)	Pattern
10.0/75-15.3	8	R4	9.00	TL	264	780	1360	420	C1C0020
10.0/75-15.3	10	R4	9.00	TL	264	780	1090	300	C1C0020
10.0/75-15.3	12	R4	9.00	TL	264	780	1180	400	C1C0020
10.0/75-15.3	14	R4	9.00	TL	264	780	1900	710	C1C0020
10.0/75-15.3	18	R4	9.00	TT	264	780	2360	710	C1C0020
11.5/80-15.3	8	R4	9.00	TL	290	867	1700	370	C1C0020
11.5/80-15.3	10	R4	9.00	TL	290	867	1360	340	C1C0020
11.5/80-15.3	12	R4	9.00	TL	290	867	2180	560	C1C0020
11.5/80-15.3	14	R4	9.00	TT/TL	290	867	1700	475	C1C0020

