

Latest data updates please go to "solidtire.apexway.com.tw".  
Other sizes are available, consult APEXWAY for further information.

2018



# OTR

## SOLID TYRE



**APEXWAY PRODUCTS CORP.**

Taiwan Head Office: 14F-5, No. 238, Shizheng N. 2nd Rd., Xitun Dist., Taichung City 40756 Taiwan, R.O.C  
Tel: +886-4-2251-2251 Fax: +886-4-2251-2129  
E-mail: apex@apexway.com.tw solidtire.apexway.com.tw



solidtire.apexway.com.tw



# WHEEL LOADER SOLID TYRE

| Size     | Pattern | Rim Width/<br>Flange Height<br>inch | O.D.<br>mm | S.W.<br>mm | T.W.<br>mm | T.D.<br>mm | Pitches | W.T.<br>kgs | Load Capacity<br>kgs@25km/h |
|----------|---------|-------------------------------------|------------|------------|------------|------------|---------|-------------|-----------------------------|
| 15.5-25  | L1H     | 11.25/2.0                           | 1270       | 390        | 380        | 107        | 22      | 355         | 7800                        |
| 16.00-25 | F1H     | 11.25/2.0                           | 1500       | 410        | 374        | 97         | 16      | 600         | 9,000                       |
|          | S1H     | 11.25/2.0                           | 1500       | 410        | *374       | *97        | -       | 640         | 10,000                      |
| 17.5-25  | F1      | 14.00/1.5                           | 1340       | 440        | 420        | 140        | 10      | 523         | 12,000                      |
|          | F1H     | 14.00/1.5                           | 1340       | 440        | 420        | 140        | 10      | 510         | 8,500                       |
|          | L1H     | 14.00/1.5                           | 1340       | 440        | 400        | 124        | 20      | 458         | 8,500                       |
|          | S1H     | 14.00/1.5                           | 1340       | 440        | *420       | *140       | -       | 525         | 9,500                       |
| 18.00-25 | S1H     | 13.00/2.5                           | 1610       | 460        | *430       | *167       | -       | 850         | 12,000                      |
|          | F1      | 17.00/2.0                           | 1480       | 520        | 496        | 160        | 10      | 781         | 14,000                      |
| 20.5-25  | F1H     | 17.00/2.0                           | 1480       | 520        | 496        | 160        | 10      | 765         | 9,600                       |
|          | S1H     | 17.00/2.0                           | 1500       | 510        | *496       | *160       | -       | 795         | 10,500                      |
| 23.5-25  | F1      | 19.50/2.5                           | 1610       | 590        | 556        | 180        | 10      | 1062        | 16,500                      |
|          | F1H     | 19.50/2.5                           | 1610       | 590        | 556        | 180        | 10      | 1042        | 12,000                      |
|          | L1H     | 19.50/2.5                           | 1620       | 580        | 520        | 167        | 20      | 965         | 12,000                      |
|          | S1H     | 19.50/2.5                           | 1610       | 590        | *556       | *180       | -       | 1085        | 13,000                      |
| 26.5-25  | F1      | 22.00/3.0                           | 1720       | 650        | 610        | 200        | 10      | 1372        | 20,500                      |
|          | F1H     | 22.00/3.0                           | 1720       | 650        | 610        | 200        | 10      | 1345        | 14,500                      |
|          | L1H     | 22.00/3.0                           | 1750       | 670        | 600        | 188        | 20      | 1353        | 14,500                      |
|          | S1H     | 22.00/3.0                           | 1720       | 650        | *610       | *200       | -       | 1380        | 16,000                      |
| 29.5-25  | F1      | 25.00/3.5                           | 1870       | 740        | 694        | 200        | 10      | 1942        | 23,000                      |
|          | F1H     | 25.00/3.5                           | 1870       | 740        | 694        | 200        | 10      | 1855        | 18,500                      |
| 35/65-33 | F1H     | 28.00/4.0                           | 2030       | 850        | 790        | 197        | 10      | 2360        | 24,000                      |



\* For Reference

# MOULD ON SOLID TYRE

| Size     | Pattern | O.D.<br>mm | S.W.<br>mm | Weight<br>kgs | Load Capacity<br>kgs@25 Km/h |
|----------|---------|------------|------------|---------------|------------------------------|
| 45x13    | F1      | 1140       | 325        | 408           | 10,000                       |
| 45x16    | F1      | 1140       | 400        | 460           | 12,500                       |
| 52x13    | F1      | 1320       | 340        | 562           | 14,500                       |
| 52x18    | F1      | 1320       | 450        | 804           | 16,500                       |
| 52x23.5  | F1      | 1320       | 605        | 1008          | 18,500                       |
| 1320x600 | F1      | 1320       | 600        | 1025          | 18,500                       |
| 1320x630 | F1      | 1320       | 630        | 1100          | 20,000                       |
| 1320x660 | F1      | 1320       | 660        | 1270          | 22,000                       |
| 1320x710 | F1      | 1320       | 710        | 1325          | 23,000                       |
| 1500x410 | F1      | 1500       | 410        | 930           | 18,000                       |
| 1516x470 | F1      | 1500       | 470        | 1000          | 20,000                       |
| 1755x455 | F1      | 1750       | 455        | 1223          | 22,000                       |
| 1755x530 | F1      | 1750       | 530        | 1450          | 25,000                       |
| 1840x580 | F1      | 1870       | 600        | 1961          | 28,000                       |

- Customized size available
- Available in Non-Marking
- Lower cost per hour
- Longer Lasting

