



**Apexway Products Corp.** has been one of the leading tire manufacturers and exporters in Taiwan.

With various capable tire and wheel production lines, Apexway provides outstanding products and efficient services that to fulfilling customer orders and needs.

**Apexway** Construction solid tire provides excellent performance, deep tread design with excellent traction ability under tough environment, tread with natural rubber compound provides advantage of resilience, increased chunk and tear resistance.

For valuable machine and operator, aperture design shows impressive cushioning during operation, will reduce equipment and operator's fatigue.

**Apexway** also provide wheel assembly service and different compound for single application to maximum the benefit of Apexway solid tire.

Since 1975  
[solidtire.apexway.com.tw](http://solidtire.apexway.com.tw)



**APEXWAY PRODUCTS CORP.**

Latest data updates please go to "[solidtire.apexway.com.tw](http://solidtire.apexway.com.tw)".  
Other sizes are available, consult APEXWAY for further information.

Tel:+886-4-2251-2251  
Fax:+886-4-2251-2129  
Taiwan Head Office: 14F-5, No. 238, Shizheng N. 2nd Rd.,  
Xitun Dist., Taichung City 40756 Taiwan, R.O.C  
E-mail:[apex@apexway.com.tw](mailto:apex@apexway.com.tw)  
[solidtire.apexway.com.tw](http://solidtire.apexway.com.tw)

2018



# SOLID TYRE



**TELEHANDLER  
SKID STEER LOADER  
AERIAL WORK PLATFORM**



# SKID STEER LOADER SOLID TYRE

# TELEHANDLER AERIAL WORK PLATFORM SOLID TYRE

Size	Pattern	Rim Width inch	O.D. mm	S.W. mm	Weight kgs	Load Capacity kgs@25km/h	Replaceable Size Of Pneumatic Tire
5.70-12	L1Hs	4.00	570	146	25.5	1300	5.70-12
23x8.5-12	L1Hs	5.00	580	190	34	1700	23x8.5-12
27x8.5-15	L1Hs	5.50	675	200	46.5	2100	27x8.5-15
27x12-15	L1Hs	8.50	675	280	69	2600	27x10.5-15
30x8.5-16	L1H	6.00	762	200	55	2000	10-16.5
30x10-16	F1H	6.00	767	240	75	2200	10-16.5
	L1H	6.00	760	240	69	2200	10-16.5
7.50-16	F1H	6.00	805	194	71	2600	10-16.5
	S1H	6.00	800	215	77	2800	10-16.5
31x10.5-16	L1H	6.00	807	235	80	2400	10-16.5
32.5x15-16	L1H	11.25	820	374	122	3600	12-16.5
8.25-16	F1H	6.00	845	212	94	3300	12-16.5
	S1Hs	6.00	838	210	90	3600	12-16.5
33x12-16	F1H	8.00	845	275	110	3200	12-16.5
	L1H	8.00	820	286	99.5	3200	12-16.5
30x10-18	L1H	7.00	767	240	62.5	2200	10-16.5
31x10.5-18	L1H	7.00	807	235	73.5	2400	10-16.5
30x10-20	L1Hs	7.00	767	240	56	2200	10-16.5
	S1Hs	7.00	767	248	68	2500	10-16.5

Size	Pattern	Rim Width inch	O.D. mm	S.W. mm	Weight kgs	Load Capacity kgs@25km/h	Replaceable Size Of Pneumatic Tire
31x10.5-20	L1H	7.00	807	235	66	2400	10-16.5
	L1H	7.00	820	250	70.5	2600	10-16.5
32x10-20	L1H	7.00	812	250	80	2900	10-16.5
	S1Hs	7.00	812	250	80	2900	12-16.5
33x12-20	L1Hs	8.00	830	285	85	3000	12-16.5
	S1Hs	8.00	820	280	93	3300	12-16.5
36.5x12-20	L1H	8.00	935	299	126	3600	14-17.5
36.5x14-20	L1H	11.00	920	350	149	4000	14-17.5
15.00-20	L1H	11.00	965	345	168	4200	14-17.5
	L1H	11.00	965	345	168	4200	355/70D17.5
38.5x14-20	L1H	11.00	970	342	170	4200	15-19.5
	L1H	11.00	970	342	170	4200	385/65D19.5
18.00-20	L1H	12.00	1060	420	265	6800	18-19.5
13.00-24	L1H	8.50	1270	320	288	6800	13.00-24
14.00-24	L1H	8.50/10.00	1340	340	365	8000	14.00-24
	S1Hs	10.00	1340	350	410	8000	14.00-24

Size	Pattern	Rim Width inch	O.D. mm	S.W. mm	Weight kgs	Load Capacity kgs@25km/h	Replaceable Size Of Pneumatic Tire
30x10-20	L1Hs	7.00	767	240	56	2200	10-16.5
33x12-20	L1H	8.00	845	285	89	3300	12-16.5
385/70-20	L1H	10.00	1060	360	227	6500	15-19.5, 385/65-22.5
445/65-20	L1H	12.00	1060	420	265	7500	18-19.5, 445/65-19.5
13.00-24	L1H	8.50	1270	320	286	6800	13.00-24
385/65-24	L1H	10.00	1060	360	192	6500	15.5-24, 385/65-22.5
14.00-24	L1H	8.50/10.00	1340	340	365	8000	14.00-24
445/65-24	L1H	12.00	1150	430	290	8500	18-22.5, 445/65-22.5

\* Other Pneumatic tire sizes please consult APEXWAY team for replacement.



L1H



L1Hs



F1H



S1H



S1Hs



L1H



L1Hs

